

MODEL: HAULSTER
TYPE: GASOLINE POWERED AUTOMATIC TRANSMISSION TRUCK
MODEL YEAR: 2010
Part No.: 84059



PRODUCT SPECIFICATION

CONFIGURATION HIGHLIGHTS

Engine: 26 hp (19.4 kW) rated, 4 cycle, 40.3 ci (660 cc) EFI, three cylinder, liquid-cooled by Suzuki

- **Valve Train:** 12 overhead valves, dual overhead cam, chain drive
- **Lubrication:** Pressurized oil system, spin-on filter
- **Air Cleaner:** Dry cartridge with evacuator valve
- **Fuel System:** Electronic fuel injection
- **Ignition:** Solid-state

Electrical: Starter, 60 Amp alternator, 12 Volt maintenance free battery (590 CCA, 85 minute reserve)

Ignition: Electronic with cam trigger, electronic advance & RPM limiter

Drive Train: 3 Speed automatic transmission. (3rd gear electronically disabled in Refresher application)

Brakes: 4 Wheel hydraulic self-adjusting drum brakes [7.9 in (20 cm) dual-servo]. Mechanical hand brake

Rear axle: Differential with hypoid gears

Capacity: Seating for 2 persons

PRODUCT OVERVIEW

| Dimensions | | Performance | |
|------------------------------|---|------------------------------|---|
| Overall Length | 136.0 in (345 cm) | Seating Capacity | 2 Persons |
| Overall Width | 53.0 in (135 cm) | Curb Weight | 1440 lb (650 kg) |
| Overall Height (No Canopy) | 51.0 in (130 cm) (Top of steering wheel) | Vehicle load capacity | 2400 lb (1090 kg) |
| Overall Height (With ROPS) | 74.0 in (188 cm) | Outside Clearance Circle | 20.2 ft (6.2 m) |
| Wheel Base | 88.2 in (224 cm) | Intersecting Aisle Clearance | N/A |
| Front Wheel Track | 42.0 in (107 cm) | Speed (Governed, Level Gnd) | 20 mph ± 0.5 mph (32 kph ± 0.8 kph) |
| Rear Wheel Track | 44.0 in (112 cm) | Towing Capacity | 2400 lb (1090 kg) |
| Gnd Clearance @ Differential | 5.0 in (13 cm) | Steering & Suspension | |
| Cargo Deck Size | 47.4 in (120 cm) W x 72 in (183 cm) L | Steering | Automotive power |
| Cargo Deck Material | Diamond pattern steel | Front Suspension | Double A-arm independent w/spring over shocks |
| Vehicle Power | | Rear Suspension | Multiple leaf springs |
| Power Source | 4 cycle, 40.3 ci (660 cc) EFI, 3 cylinder | Rear Axle | Differential with hypoid gears |
| Valve Train | 12 valve, dual OHV/OHC. Chain drive | Service Brake | 4 Wheel 7.9 (20 cm) hydraulic drum |
| Horsepower (kW) | 26.0 hp (19.4 kW) @ 3600 rpm (governed) | Parking Brake | Mechanical hand brake |
| Electrical System | 12 Volt starter. 60 amp alternator | Front Tires | USA Trail 20.5 x 8 - 10 (Load range C) |
| Battery (Qty, Type) | One 12 Volt maintenance free | Rear Tires | USA Trail 20.5 x 8 - 10 (Load range C) |
| Key or Pedal Start | Key start | Body & Chassis | |
| Air Cleaner | Dry cartridge | Frame | Unitized welded steel channel. E-coat finish |
| Lubrication | Pressurized oil system | Front Body & Finish | Polyethylene |
| Oil Filter | Spin-on | Rear Body & Finish | Steel with rubber fender flairs |
| Cooling System | Liquid cooled | Storage | Hinged front cowl |
| Fuel Capacity | 7.0 gallon (26.5 L) tank | Standard Color | Yellow |
| Transmission | 3 Speed automatic | | |
| Gear Selection | Neutral - Reverse - Park | | |
| Gear Shift location | Dash | | |
| Rear Axle Ratio | 11.16:1 | | |

Some items shown may be optional equipment

OPTIONS & FIELD INSTALLED ACCESSORIES (Installation not included)*

| Item | Std | Opt | Fld | Item | Std | Opt | Fld |
|--|-----|-----|-----|---|-----|-----|-----|
| TIRES & WHEELS | | | | WEATHER PROTECTION: | | | |
| Front & Rear: | | | | Cab (includes ROPS, windshield wiper, front & rear windows) | | | |
| USA Trail 20.5 x 8 - 10 (Load range C) | ● | | | Doors (Cab required) Hunter Green | | | ● |
| COLORS: | | | | Doors (Cab required) Yellow | | | |
| Body Color (Yellow) | ● | | | Doors (Cab required) White | | | ● |
| Body Color (White) | | ● | | Doors (Cab required) Red | | | ● |
| Body Color (Hunter Green) | | ● | | CUSTOM REQUIREMENTS: | | | |
| Body Color (Red) | | ● | | Contact Innovative Designs @ 800 241-5855 X 5972 for quote of individual customer needs | | | |
| Custom Body Color | | ● | | | | | |
| OTHER PERFORMANCE: | | | | | | | |
| Front Bumper | | ● | | | | | |
| Heater/Defroster | | ● | | | | | |
| Rear shock absorbers | | ● | | | | | |
| Rear View Mirrors (outside, qty 2) | | ● | | | | | |
| ROPS (Roll Over Protection, black with seat belts) | | ● | | | | | |
| Spark Arrestor | | | ● | | | | |
| HAULING & TOWING: | | | | | | | |
| Box sides & tailgate | | ● | | | | | |
| Pintle hitch (requires rear bumper) | | ● | | | | | |
| Rear Bumper | | ● | | | | | |
| Tow hitch (requires rear bumper) | | ● | | | | | |
| ELECTRICAL: | | | | | | | |
| 12 Volt Outlet | ● | | | | | | |
| Back-up alarm | | ● | | | | | |
| Battery level gauge | ● | | | | | | |
| Brake Lights | ● | | | | | | |
| Dome Light (Cab Required) | | ● | | | | | |
| Fuel gauge | ● | | | | | | |
| Headlights | ● | | | | | | |
| Horn | ● | | | | | | |
| Hour meter | ● | | | | | | |
| Low fluid indicator | ● | | | | | | |
| Low oil pressure gauge | ● | | | | | | |
| Park brake Indicator | ● | | | | | | |
| Speedometer | | ● | | | | | |
| Tachometer | ● | | | | | | |
| Taillights | ● | | | | | | |
| Temperature gauge | ● | | | | | | |
| Turn Signals with 4-Way Flashers | | ● | | | | | |
| Volt meter | ● | | | | | | |
| | | | | | | | |
| | | | | | | | |
| | | | | | | | |
| | | | | | | | |
| | | | | | | | |
| | | | | | | | |
| | | | | | | | |
| | | | | | | | |
| | | | | | | | |
| | | | | | | | |

MODEL: HAULSTER
TYPE: HIGH SPEED GASOLINE POWERED
MANUAL TRANSMISSION TRUCK
MODEL YEAR: 2010
Part No.: 84060



PRODUCT SPECIFICATION

CONFIGURATION HIGHLIGHTS

- Engine:** 32.2 hp (24.0 kW) rated, 4 cycle, 40.3 cid (660 cc) EFI, three cylinder, liquid-cooled by Suzuki
- **Valve Train:** 12 overhead valves, dual overhead cam, chain drive
 - **Lubrication:** Pressurized oil system, spin-on filter 3.3 qt (3 L) capacity
 - **Air Cleaner:** Dry cartridge with evacuator valve
 - **Fuel System:** Electronic fuel injection
 - **Ignition:** Solid-state
- Electrical:** Starter, 60 amp alternator, 12 Volt maintenance free battery (580 cca, 85 minute reserve)
- Ignition:** Electronic with cam trigger, electronic advance & RPM limiter
- Drive Train:** 5 Speed manual transmission. Low creeper first gear. All forward gears synchronized
- Clutch:** 6.7 in (17 cm) dry single disc & pressure plate
- Brakes:** 4-wheel hydraulic self-adjusting drum brakes [7.9 in (20 cm) dual-servo] Dual master cylinder with remote reservoir, Mechanical hand brake
- Rear Axle:** Differential with hypoid gears
- Capacity:** Seating for 2 persons

PRODUCT OVERVIEW

Dimensions

| | |
|---------------------------------|---------------------------------------|
| Overall Length | 136.0 in (345 cm) |
| Overall Width | 53.0 in (135 cm) |
| Overall Height (to top of ROPS) | 74.0 in (188 cm) |
| Wheel Base | 88.2 in (224 cm) |
| Front Wheel Track | 42.0 in (107 cm) |
| Rear Wheel Track | 44.0 in (112 cm) |
| Gnd Clearance @ Differential | 5.0 in (13 cm) |
| Cargo Deck Size | 47.4 in (120 cm) W x 72 in (183 cm) L |
| Cargo Deck Material | Diamond pattern steel |

Vehicle Power

| | |
|---------------------|---|
| Power Source | 4 cycle, 40.3 ci (660 cc) EFI, 3 cylinder |
| Valve Train | 12 valve, dual OHV/OHC. Chain drive |
| Horsepower (kW) | 32.2 hp (24.0 kW) @ 4450 rpm (governed) |
| Electrical System | 12 Volt starter. 60 amp alternator |
| Battery (Qty, Type) | One 12 Volt maintenance free |
| Key or Pedal Start | Key start |
| Air Cleaner | Dry cartridge |
| Lubrication | Pressurized oil system |
| Oil Filter | Spin-on |
| Cooling System | Liquid cooled |
| Fuel Capacity | 7.0 gallon (26.5 L) tank |
| Transmission | Synchronized 5 Speed manual |
| Gear Selection | 5 speeds forward - Neutral - Reverse |
| Gear Shift location | Dash |
| Rear Axle Ratio | 11.16:1 |

Performance

| | |
|------------------------------|---------------------------------------|
| Seating Capacity | 2 Persons |
| Curb Weight | 1540 lb (699 kg) |
| Vehicle load capacity | 2400 lb (1090 kg) |
| Outside Clearance Circle | 20.2 ft (6.2 m) |
| Intersecting Aisle Clearance | N/A |
| Speed (Governed, Level Gnd) | 25.5 mph ± 0.5 mph (41 kph ± 0.8 kph) |
| Towing Capacity | 2400 lb (1090 kg) |

Steering & Suspension

| | |
|------------------|---|
| Steering | Automotive power |
| Front Suspension | Double A-arm independent w/spring over shocks |
| Rear Suspension | Multiple leaf springs |
| Rear Axle | Differential with hypoid gears |
| Service Brake | 4 Wheel 7.9 (20 cm) hydraulic drum |
| Parking Brake | Mechanical hand brake |
| Front Tires | USA Trail 20.5 x 8 - 10 (Load range C) |
| Rear Tires | USA Trail 20.5 x 8 - 10 (Load range C) |

Body & Chassis

| | |
|--------------------------------|--|
| Frame | Unitized welded steel channel. E-coat finish |
| Front Body & Finish | Polyethelene |
| Rear Body & Finish | Steel with rubber fender flairs |
| Storage | Hinged front cowl |
| Standard Color | Yellow |
| Roll Over Protective Structure | 2 post ROPS - standard |

Some items shown may be optional equipment

OPTIONS & FIELD INSTALLED ACCESSORIES (Installation not included)*

| Item | Std | Opt | Fld | Item | Std | Opt | Fld |
|--|-----|-----|-----|---|-----|-----|-----|
| TIRES & WHEELS | | | | CUSTOM REQUIREMENTS: | | | |
| Front & Rear: | | | | Contact Innovative Designs @ 800 241-5855 X 5972 for quote of individual customer needs | | | |
| USA Trail 20.5 x 8 - 10 (Load range C) | ● | | | | | | |
| COLORS: | | | | | | | |
| Body Color (Yellow) | ● | | | | | | |
| Body Color (Hunter Green) | | ● | | | | | |
| Body Color (White) | | ● | | | | | |
| Body Color (Red) | | ● | | | | | |
| Custom Body Color | | ● | | | | | |
| OTHER PERFORMANCE: | | | | | | | |
| Front Bumper | | ● | | | | | |
| Rear shock absorbers | | ● | | | | | |
| ROPS (Roll Over Protection, black with seat belts) | ● | | | | | | |
| Spark Arrestor | | | ● | | | | |
| HAULING & TOWING: | | | | | | | |
| Box sides & tailgate | | ● | | | | | |
| Pintle hitch (requires rear bumper) | | ● | | | | | |
| Rear Bumper | | ● | | | | | |
| Tow hitch (requires rear bumper) | | ● | | | | | |
| ELECTRICAL: | | | | | | | |
| 12 Volt Outlet | ● | | | | | | |
| Back-up alarm | | ● | | | | | |
| Battery level gauge | ● | | | | | | |
| Brake Lights | ● | | | | | | |
| Fuel gauge | ● | | | | | | |
| Headlights | ● | | | | | | |
| Horn | ● | | | | | | |
| Hour meter | ● | | | | | | |
| Low fluid indicator | ● | | | | | | |
| Low oil pressure gauge | ● | | | | | | |
| Park brake Indicator | ● | | | | | | |
| Speedometer | | ● | | | | | |
| Tachometer | ● | | | | | | |
| Taillights | ● | | | | | | |
| Temperature gauge | ● | | | | | | |
| Volt meter | ● | | | | | | |
| | | | | | | | |
| | | | | | | | |
| | | | | | | | |
| | | | | | | | |
| | | | | | | | |

MODEL: HAULSTER
TYPE: DIESEL POWERED MANUAL TRANSMISSION TRUCK
MODEL YEAR: 2010
Part No.: 84065



PRODUCT SPECIFICATION

CONFIGURATION HIGHLIGHTS

Engine: 24.8 hp (18.5 kW) rated, 4 cycle, 69 cid (1123 cc) EFI, three cylinder, liquid-cooled Kubota D1105 Diesel

- **Fuel System:** Indirect
- **Lubrication:** Pressurized oil system, spin-on filter 1.35 gal (5.1 L) capacity
- **Air Cleaner:** Dry cartridge with evacuator valve

Electrical: Starter, 60 amp alternator, 12 Volt maintenance free battery (590 cca, 85 minute reserve)

Acceptable Fuel: N590 Diesel fuel types - Auto / C0 / C1 / C2 / C3 / C4, BS2869 Class A2, ASTM D 975-92 Class 1, 2 and 3 & special grade 3
or
Low Sulphur Diesel (LSD S500) & Ultra Low Sulphur Diesel (USLD S15)
or
Bio-diesel - R.M.E. meeting DIN V 51606, Up to 5% RME. No mixture above 5% is acceptable

Drive Train: 4-speed manual transmission. Low creeper first gear. All forward gears synchronized

Clutch: 7.1 in (18 cm) dry single disc & pressure plate

Brakes: 4-wheel hydraulic self-adjusting drum brakes [7.9 in (20 cm) dual-servo] Dual master cylinder with remote reservoir, Mechanical hand brake

Rear Axle: Differential with hypoid gears

Capacity: Seating for 2 persons

PRODUCT OVERVIEW

Dimensions

| | |
|------------------------------|--|
| Overall Length | 136.0 in (345 cm) |
| Overall Width | 53.0 in (135 cm) |
| Overall Height (No Canopy) | 51.0 in (130 cm) (Top of steering wheel) |
| Overall Height (With ROPS) | 74.0 in (188 cm) |
| Wheel Base | 88.2 in (224 cm) |
| Front Wheel Track | 42.0 in (107 cm) |
| Rear Wheel Track | 44.0 in (112 cm) |
| Gnd Clearance @ Differential | 5.0 in (13 cm) |
| Cargo Deck Size | 47.4 in (120 cm) W x 72 in (183 cm) L |
| Cargo Deck Material | Diamond pattern steel |

Vehicle Power

| | |
|---------------------|---|
| Power Source | 3 Cylinder Liquid-Cooled Kubota Diesel |
| Horsepower (kW) | 24.8 hp (18.5 kW) @ 3000 rpm (governed) |
| Electrical System | 12 Volt starter. 60 amp alternator |
| Battery (Qty, Type) | One 12 Volt maintenance free |
| Key or Pedal Start | Key start |
| Air Cleaner | Dry cartridge |
| Lubrication | Pressurized oil system |
| Oil Filter | Spin-on |
| Cooling System | Liquid cooled |
| Fuel Capacity | 7.0 gallon (26.5 L) tank |
| Transmission | Synchronized 4 Speed manual |
| Gear Selection | 4 speeds forward - Neutral - Reverse |
| Gear Shift location | Dash |

| | |
|---------------------|---------|
| Rear Axle Ratio | 11.16:1 |
| Gear Shift location | Dash |

Performance

| | |
|------------------------------|---------------------------------------|
| Seating Capacity | 2 Persons |
| Curb Weight | 1570 lb (710 kg) |
| Vehicle load capacity | 2400 lb (1090 kg) |
| Outside Clearance Circle | 20.2 ft (6.2 m) |
| Intersecting Aisle Clearance | N/A |
| Speed (Governed, Level Gnd) | 17.5 mph ± 0.5 mph (28 kph ± 0.8 kph) |
| Towing Capacity | 2400 lb (1090 kg) |

Steering & Suspension

| | |
|------------------|---|
| Steering | Automotive power |
| Front Suspension | Double A-arm independent w/spring over shocks |
| Rear Suspension | Multiple leaf springs |
| Rear Axle | Differential with hypoid gears |
| Service Brake | 4 Wheel 7.9 (20 cm) hydraulic drum |
| Parking Brake | Mechanical hand brake |
| Front Tires | USA Trail 20.5 x 8 - 10 (Load range C) |
| Rear Tires | USA Trail 20.5 x 8 - 10 (Load range C) |

Body & Chassis

| | |
|---------------------|--|
| Frame | Unitized welded steel channel. E-coat finish |
| Front Body & Finish | Polyethelene |
| Rear Body & Finish | Steel with rubber fender flairs |
| Storage | Hinged front cowl |
| Standard Color | Yellow |

Some items shown may be optional equipment

OPTIONS & FIELD INSTALLED ACCESSORIES (Installation not included)*

| Item | Std | Opt | Fld | Item | Std | Opt | Fld |
|--|-----|-----|-----|---|-----|-----|-----|
| TIRES & WHEELS | | | | WEATHER PROTECTION: | | | |
| Front & Rear: | | | | Cab (includes ROPS, windshield wiper, front & rear windows) | | | |
| USA Trail 20.5 x 8 - 10 (Load range C) | ● | | | Doors (Cab required) Hunter Green | | | ● |
| COLORS: | | | | Doors (Cab required) Yellow | | | |
| Body Color (Yellow) | ● | | | Doors (Cab required) White | | | ● |
| Body Color (Hunter Green) | | ● | | Doors (Cab required) Red | | | ● |
| Body Color (White) | | ● | | CUSTOM REQUIREMENTS: | | | |
| Body Color (Red) | | ● | | Contact Innovative Designs @ 800 241-5855 X 5972 for quote of individual customer needs | | | |
| Custom Body Color | | ● | | | | | |
| OTHER PERFORMANCE: | | | | | | | |
| Front Bumper | | ● | | | | | |
| Heater/Defroster | | ● | | | | | |
| Rear shock absorbers | | ● | | | | | |
| Rear View Mirrors (outside, qty 2) | | ● | | | | | |
| ROPS (Roll Over Protection, black with seat belts) | | ● | | | | | |
| Spark Arrestor | | | ● | | | | |
| HAULING & TOWING: | | | | | | | |
| Box sides & tailgate | | ● | | | | | |
| Pintle hitch (requires rear bumper) | | ● | | | | | |
| Rear Bumper | | ● | | | | | |
| Tow hitch (requires rear bumper) | | ● | | | | | |
| ELECTRICAL: | | | | | | | |
| 12 Volt Outlet | ● | | | | | | |
| Back-up alarm | | ● | | | | | |
| Battery level gauge | ● | | | | | | |
| Brake Lights | ● | | | | | | |
| Dome Light (Cab Required) | | ● | | | | | |
| Fuel gauge | ● | | | | | | |
| Headlights | ● | | | | | | |
| Horn | ● | | | | | | |
| Hour meter | ● | | | | | | |
| Low fluid indicator | ● | | | | | | |
| Low oil pressure gauge | ● | | | | | | |
| Park brake Indicator | ● | | | | | | |
| Speedometer | | ● | | | | | |
| Tachometer | ● | | | | | | |
| Taillights | ● | | | | | | |
| Temperature gauge | ● | | | | | | |
| Turn Signals with 4-Way Flashers | | ● | | | | | |
| Volt meter | ● | | | | | | |
| | | | | | | | |
| | | | | | | | |
| | | | | | | | |
| | | | | | | | |
| | | | | | | | |
| | | | | | | | |
| | | | | | | | |
| | | | | | | | |
| | | | | | | | |
| | | | | | | | |

MODEL: HAULSTER
TYPE: GASOLINE POWERED MANUAL TRANSMISSION TRUCK
MODEL YEAR: 2010
Part No.: 84058



PRODUCT SPECIFICATION

CONFIGURATION HIGHLIGHTS

- Engine:** 26 hp (19.4 kW) rated, 4 cycle, 40.3 cid (660 cc) EFI, three cylinder, liquid-cooled by Suzuki
- **Valve Train:** 12 overhead valves, dual overhead cam, chain drive
 - **Fuel System:** Electronic fuel injection
 - **Lubrication:** Pressurized oil system, spin-on filter 3.3 qt (3 L) capacity
 - **Ignition:** Solid-state
 - **Air Cleaner:** Dry cartridge with evacuator valve
- Electrical:** Starter, 60 amp alternator, 12 Volt maintenance free battery (580 cca, 85 minute reserve)
- Ignition:** Electronic with cam trigger, electronic advance & RPM limiter
- Drive Train:** 5 Speed manual transmission. Low creeper first gear. All forward gears synchronized
- Clutch:** 6.7 in (17 cm) dry single disc & pressure plate
- Brakes:** 4-wheel hydraulic self-adjusting drum brakes [7.9 in (20 cm) dual-servo] Dual master cylinder with remote reservoir, Mechanical hand brake
- Rear Axle:** Differential with hypoid gears
- Capacity:** Seating for 2 persons

PRODUCT OVERVIEW

Dimensions

| | |
|------------------------------|--|
| Overall Length | 136.0 in (345 cm) |
| Overall Width | 53.0 in (135 cm) |
| Overall Height (No Canopy) | 51.0 in (130 cm) (Top of steering wheel) |
| Overall Height (With ROPS) | 74.0 in (188 cm) |
| Wheel Base | 88.2 in (224 cm) |
| Front Wheel Track | 42.0 in (107 cm) |
| Rear Wheel Track | 44.0 in (112 cm) |
| Gnd Clearance @ Differential | 5.0 in (13 cm) |
| Cargo Deck Size | 47.4 in (120 cm) W x 72 in (183 cm) L |
| Cargo Deck Material | Diamond pattern steel |

Vehicle Power

| | |
|---------------------|---|
| Power Source | 4 cycle, 40.3 ci (660 cc) EFI, 3 cylinder |
| Valve Train | 12 valve, dual OHV/OHC. Chain drive |
| Horsepower (kW) | 26.0 hp (19.4 kW) @ 3600 rpm (governed) |
| Electrical System | 12 Volt starter. 60 amp alternator |
| Battery (Qty, Type) | One 12 Volt maintenance free |
| Key or Pedal Start | Key start |
| Air Cleaner | Dry cartridge |
| Lubrication | Pressurized oil system |
| Oil Filter | Spin-on |
| Cooling System | Liquid cooled |
| Fuel Capacity | 7.0 gallon (26.5 L) tank |
| Transmission | Synchronized 5 Speed manual |
| Gear Selection | 5 speeds forward - Neutral - Reverse |
| Gear Shift location | Dash |
| Rear Axle Ratio | 11.16:1 |

Performance

| | |
|------------------------------|-------------------------------------|
| Seating Capacity | 2 Persons |
| Curb Weight | 1440 lb (650 kg) |
| Vehicle load capacity | 2400 lb (1090 kg) |
| Outside Clearance Circle | 20.2 ft (6.2 m) |
| Intersecting Aisle Clearance | N/A |
| Speed (Governed, Level Gnd) | 20 mph ± 0.5 mph (32 kph ± 0.8 kph) |
| Towing Capacity | 2400 lb (1090 kg) |

Steering & Suspension

| | |
|------------------|---|
| Steering | Automotive power |
| Front Suspension | Double A-arm independent w/spring over shocks |
| Rear Suspension | Multiple leaf springs |
| Rear Axle | Differential with hypoid gears |
| Service Brake | 4 Wheel 7.9 (20 cm) hydraulic drum |
| Parking Brake | Mechanical hand brake |
| Front Tires | USA Trail 20.5 x 8 - 10 (Load range C) |
| Rear Tires | USA Trail 20.5 x 8 - 10 (Load range C) |

Body & Chassis

| | |
|---------------------|--|
| Frame | Unitized welded steel channel. E-coat finish |
| Front Body & Finish | Polyethelene |
| Rear Body & Finish | Steel with rubber fender flairs |
| Storage | Hinged front cowl |
| Standard Color | Yellow |

Some items shown may be optional equipment

OPTIONS & FIELD INSTALLED ACCESSORIES (Installation not included)*

| Item | Std | Opt | Fld | Item | Std | Opt | Fld |
|--|-----|-----|-----|---|-----|-----|-----|
| TIRES & WHEELS | | | | WEATHER PROTECTION: | | | |
| Front & Rear: | | | | Cab (includes ROPS, windshield wiper, front & rear windows) | | | |
| USA Trail 20.5 x 8 - 10 (Load range C) | ● | | | Doors (Cab required) Hunter Green | | | ● |
| COLORS: | | | | Doors (Cab required) Yellow | | | |
| Body Color (Yellow) | ● | | | Doors (Cab required) Red | | | ● |
| Body Color (White) | | ● | | Doors (Cab required) White | | | ● |
| Body Color (Hunter Green) | | ● | | CUSTOM REQUIREMENTS: | | | |
| Body Color (Red) | | ● | | Contact Innovative Designs @ 800 241-5855 X 5972 for quote of individual customer needs | | | |
| Custom Body Color | | ● | | | | | |
| OTHER PERFORMANCE: | | | | | | | |
| Front Bumper | | ● | | | | | |
| Heater/Defroster | | ● | | | | | |
| Rear View Mirrors (outside, qty 2) | | ● | | | | | |
| ROPS (Roll Over Protection, black with seat belts) | | ● | | | | | |
| Spark Arrestor | | | ● | | | | |
| HAULING & TOWING: | | | | | | | |
| Box sides & tailgate | | ● | | | | | |
| Pintle hitch (requires rear bumper) | | ● | | | | | |
| Rear Bumper | | ● | | | | | |
| Tow hitch (requires rear bumper) | | ● | | | | | |
| ELECTRICAL: | | | | | | | |
| 12 Volt Outlet | ● | | | | | | |
| Back-up alarm | | ● | | | | | |
| Battery level gauge | ● | | | | | | |
| Brake Lights | ● | | | | | | |
| Dome Light (Cab Required) | | ● | | | | | |
| Fuel gauge | ● | | | | | | |
| Headlights | ● | | | | | | |
| Horn | ● | | | | | | |
| Hour meter | ● | | | | | | |
| Low fluid indicator | ● | | | | | | |
| Low oil pressure gauge | ● | | | | | | |
| Park brake Indicator | ● | | | | | | |
| Speedometer | | ● | | | | | |
| Tachometer | ● | | | | | | |
| Taillights | ● | | | | | | |
| Temperature gauge | ● | | | | | | |
| Turn Signals with 4-Way Flashers | | ● | | | | | |
| Volt meter | ● | | | | | | |
| | | | | | | | |
| | | | | | | | |
| | | | | | | | |
| | | | | | | | |