



A Textron Company

MODEL: ST SPORT II
TYPE: ELECTRIC POWERED TRUCK
MODEL YEAR: 2010

Part No.: 608389



PRODUCT SPECIFICATION

CONFIGURATION HIGHLIGHTS

Precision Drive System™ (PDS): Programmable to terrain

- Solid State continuously variable separately excited speed controller
- Dash mounted direction selector switch (Forward-Neutral-Reverse)
- Anti-roll back, walkaway braking and alarm
- Regenerative 'Pedal Down' and/or 'Pedal Up' braking
- Six, 6 Volt Deep Cycle Batteries
- Full torque, reduced speed reverse
- Inductive throttle sensor
- Audible diagnostic mode

Battery Charger: PowerWise™ 36QE high frequency, fully line compensating, 10 ft (3 m) DC Cord. Underwriters Lab. (U.L.) Listed, (C.S.A. Certified)

- **Input:** 110 – 120 Volt, 50/60 Hz, 8 amp
- **Output:** 36 Volt at 16 amps DC

Motor: 36 Volt DC shunt wound, brazed armature, solid copper windings

Drive Train: Direct motor shaft connected to transaxle pinion shaft

Electrical System: 36 Volt DC, six, 6 volt deep cycle batteries (115 minute minimum, 225 amp-hour @ 20 hr. discharge rate)

Transaxle: Differential with helical gears

Brakes: Dual rear wheel mechanical self-adjusting drum brakes. Automatic single point park brake release with self-compensating system

Capacity: Seating for 2 persons.

PRODUCT OVERVIEW

Dimensions

Overall Length	103.0 in (260 cm)
Overall Width	46.5 in (118 cm)
Overall Height (No Canopy)	49.0 in (124 cm) (Top of steering wheel)
Overall Height (With Canopy)	78.0 in (183 cm)
Wheel Base	65.5 in (166 cm)
Front Wheel Track	37.0 in (94 cm)
Rear Wheel Track	38.0 in (97 cm)
Gnd Clearance @ Differential	5.5 in (15 cm)
Cargo Box Width (inside)	44.5 in (113 cm)
Cargo Box Length (inside)	30.5 in (77 cm)
Cargo Box Depth (inside)	7.5 in (19 cm)
Cargo Box Capacity	5.9 cu ft (0.17 m3)
Cargo Box Material	Roto-molded polyethylene

Vehicle Power

Power Source	36 Volts DC
Motor Type	Shunt Wound
Horsepower (kW)	2.5 HP Continuous
Electrical System	36 Volt
Batteries (Qty, Type)	Six, 6 Volt Deep Cycle
Key or Pedal Start	Pedal Start
Battery Charger	36 VDC PowerWise™ QE, 120 VAC, UL/CSA
Speed Controller	300 Amp Precision Drive System (PDS)
Drive Train	Motor Shaft Direct Drive

Transaxle	Differential with helical gears
Gear Selection	Dash Mounted Forward-Neutral-Reverse
Rear Axle Ratio	12.44:1

Performance

Seating Capacity	2 Person
Dry Weight	675 lb (310 kg) (Without Batteries)
Curb Weight	1040 lb (64 kg)
Bed Load Capacity	500 lb (230 kg)
Vehicle load capacity	800 lb (360 kg)
Outside Clearance Circle	18.9 ft (5.76 m)
Intersecting Aisle Clrnce	N/A
Speed (Level Ground)	13 mph ± 0.5 mph (21 kph ± 0.8 kph)
Towing Capacity	500 lb (230 kg) max load

Steering & Suspension

Steering	Self-compensating rack and pinion
Front Suspension	Leaf springs with hydraulic shock absorbers
Rear Suspension	Leaf springs with hydraulic shock absorbers
Service Brake	Rear wheel mechanical self-adjusting drum
Parking Brake	Self-compensating, single point engagement
Front Tires	Trail Wolf 20 x 11 - 10 (4 Ply Rated) Uni-directional
Rear Tires	Trail Wolf 20 x 11 - 10 (4 Ply Rated) Uni-directional

Body & Chassis

Frame	Welded steel with DuraShield™ powder coat
Front Body & Finish	Injection molded TPO
Rear Body & Finish	Steel. Base coat/clear coat
Standard Color	Black

Some items shown may be optional equipment

